

F24-60

Joystick Controller

Double Joystick with 5 steps

Reliable - High Performance - Economic

F24-60 series is particular suitable for control of Tower Cranes, Overhead Cranes and Concrete Pumps. This particular model is equipped with most sophisticated safety features for making the entire operation safe.



Features

- Fully programmable relay configuration with maximum 16 relays output per command. (NO extra extension unit required)
- Durable nylon-fiber housing for extra shock resistance.
- Operating range up to 100 meters.
- Pre-wiring standard cable making installation quick and easy.
- New waist belt provide maximum comfort for operator (Optional)
- 3 stages LED battery power indicator
- Acceleration delay time control (Providing smooth moving for multiple speeds cranes)
- Safety features:
 - ▶ 4.3 billion unique ID code
 - ▶ Hamming code
 - ▶ Enhanced Watch-Dog circuit



Transmitter

- Double Joystick/ 6 Single step buttons (Including start button)
- 1 Emergency button (EMS)
- 1 Rotary key switch
- 4 selector switches

Receiver

- Max. 40 relay output (Programmable)
- NC/NO relay (optional)
- External passive antenna (optional)

General Specification

Operating Temp	-35°C ~ +80°C
Operating Range	100 M
Transmitter power supply	4 AA size Alkaline / Rechargeable Battery
Receiver power supply	AC 48/110/220/380 V
Protection class	IP 65 Industrial standard
ID Code	4.3 billion (32 bit)
Hamming distance	≥ 4
TX Dimension & Weight	220 x 110 x 90 mm Apprx.860g(w/o batteries)
RX Dimension & Weight	290 x 230 x 70 mm Apprx.2200g(w/o cable)

F24-60 Accesories



CD Software
& Program Cable



Copier



Battery Charger



Passive Antenna



Waist belt